

Tenda



RX1 Pro

Dual Band Wi-Fi 6 Router



RX1 Pro

Dual Band Wi-Fi 6 Router

Products Description

RX1 Pro is a signal-enhanced dual-band Wi-Fi 6 router designed for home users. It supports Wi-Fi 6 (802.11ax) technology on the 5GHz frequency band, making the connection of smart devices smoother and faster. Upgrade OFDMA+MU-MIMO technology to simultaneously meet more devices accessing the Internet, improve transmission efficiency, and reduce delay. A high-performance signal enhancement module and 5 external 6dBi high-gain antennas bring a longer propagation distance.

Selling Points

The logo for Wi-Fi 6, featuring the text "Wi-Fi 6" in a bold, sans-serif font. The "6" is significantly larger and bolder than the other characters, and is contained within a dark rectangular box. The entire logo is set against a white background within a square frame.

Upgrade to Wi-Fi 6 For a Faster Network Experience

RX1 Pro supports next-gen Wi-Fi 6, providing a wireless network experience with faster transmission and lower latency.



Eliminating Dead Zone

With 5 external 6dBi high-gain antennas and the high-performance signal enhancement module, RX1 Pro easily achieves whole-house Wi-Fi 6 coverage for medium and large households.



Minimize Lag in Multi-user Scenario

Significantly improve network performance and efficiency with MU-MIMO + OFDMA technology, meeting the needs of household members to surf the Internet simultaneously without latency.



Easy Setup in 3 Steps

Automatic recognition of modem connection type to reduce setup steps. Installation can be done with just a few clicks.

Technical Specifications

Hardware features	
Standard&Protocol	IEEE802.3, IEEE802.3u, IEEE802.3ab
Interface	10/100Mbps WAN Ports*1 10/100Mbps LAN Ports*3
Antenna	5*6dBi External Antennas
Button	1*WPS/Reset Button
Power	Input: AC 100~240V~50/60Hz Output:DC 12V ---1A
LED indicator	1 * LED
Wireless features	
Wireless Standards	5GHz: IEEE 802.11 ax/ac/a/n 2.4GHz:IEEE 802.11 b/g/n
Frequency	2.4GHz & 5GHz
Data Rate	5GHz:1201Mbps 2.4GHz:300Mbps
Basic Functions	OFDMA MU-MIMO Beamforming Signal Directional Transmission Technology
Wireless Security	WPA2-PSK, WPA3-SAE, WPA3-SAE/WPA2-PSK Wireless Encryption Disable and Enable WPS Fast Connection
Software Function	
Internet Connection Type	PPPOE, Dynamic IP, Static IP
Network Protocol	IPv4&IPv6
Operating Mode	Wireless Router Mode Wireless Relay Mode (Client+AP) AP Mode
DHCP	DHCP Server DHCP Client List DHCP Static IP Address Reservation and Assignment
Security	Client Filter Parental Control Remote Web Management

Technical Specifications

Software Function	
Firewall	<ul style="list-style-type: none"> ICMP Flood Attack Defense TCP Flood Attack Defense UDP Flood Attack Defense Ignore Ping Packet From WAN Port
DDNS	Support DynDNS, No-ip
Special Features	<ul style="list-style-type: none"> WPA3 Unify 2.4 GHz & 5 GHz Smart LED On/Off Tenda Wi-Fi App TR069
Features	<ul style="list-style-type: none"> IPTV IPv6 Dual Frequency In One Bandwidth Control Guest Network Static Routing System Log Remote Web Management MAC Clone Broadband Account Migration Backup & Restore Configurations Support Automatic Access Detection Firmware Upgrade Online
Other Features	
Temperature	<ul style="list-style-type: none"> Operating Temperature : 0°C~40°C Storage Temperature : -40C ~70°C
Humidity	<ul style="list-style-type: none"> Operating Humidity : 10 %~90% RH non-condensing Storage Humidity : 5 %~ 90%RH non-condensing
Certification	CE, RoHS, FCC
Admin Page	Default Access Address: tendawifi.com or http://192.168.0.1
Package Content	<ul style="list-style-type: none"> Wireless Router*1 Ethernet Cable*1 Power Adapter*1 Installation Guide*1

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

Tenda Technology Bldg.Int' I E-City,
#1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen China.

E-mail:support@tenda.com.cn

Tel:+86-755-2765 7098

Fax:+86-755-2765 7178

PC:518055

